



AUDIX Technology (Shenzhen) Co., Ltd.
52 Block, Shenzhen Science & Industry Park,
Nantou, Shenzhen, Guangdong, China

Tel : 0755-26639495 6-7
Fax : 86 0755-26632877

Certificate of Compliance

No. ACS-E09156

The following products have been tested by us with the listed standards and found in compliance with the council EMC directive 2004/108/EC. It is demonstrative for the compliance with this EMC Directive.

Submittor : Acer Incorporated
8F, 88, Sec. 1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan,
R.O.C.
Product : Personal Computer

Brand Name	Model No.
acer	Aspire M3800; Aspire M1800; Aspire M1202; Aspire M3202; Aspire M5800; Aspire M5801; Aspire M5800G; Aspire M3800G; Aspire M5202
Gateway	DX4820; DX4300
Packard Bell	ixtreme M5720; ixtreme M5120

Test Standards :

EN55022: 2006	Limits and methods of measurement of radio disturbance characteristics of information technology equipment
EN61000-3-2: 2006	Electromagnetic compatibility(EMC) Part 3 :Limits Section 2 : Limits for harmonic current emissions (equipment input current $\leq 16A$ per phase)
EN61000-3-3: 1995+A1: 2001+A2: 2005	Electromagnetic compatibility(EMC) Part 3 :Limits Section 3 : Limits of voltage fluctuations and flicker in low-voltage supply systems for equipment with rated current $\leq 16A$
EN55024: 1998+A1: 2001+A2: 2003	Information technology equipment-Immunity characteristics limits and methods of measurement
IEC 61000-4-2: 2001	Electrostatic discharge
IEC 61000-4-3: 2006	RF Field Strength susceptibility
IEC61000-4-4: 2004+Cor 1: 2006+Cor 2: 2007	Electrical Fast transients
IEC 61000-4-5: 2005	Surge
IEC61000-4-6: 2003+A1:2004+A2:2006	Conducted Susceptibility
IEC 61000-4-11: 2004	Dips / Voltage Interruption Variation

Stamp only for EMC Dept Report

Signature:

Ken Lu
Manager

Date : Apr.15, 2009



The statement is based on a single evaluation of one sample of above mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab. logo.

Certificate of Compliance

No. ACS-E09156

The following products have been tested by us with the listed standards and found in compliance with the R&TTE directive 1999/5/EC Article 3(1)(b)

Submittor : Acer Incorporated
8F, 88, Sec. 1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan,
R.O.C.
Product : Personal Computer

Brand Name	Model No.
acer	Aspire M3800; Aspire M1800; Aspire M1202; Aspire M3202; Aspire M5800; Aspire M5801; Aspire M5800G; Aspire M3800G; Aspire M5202
Gateway	DX4820; DX4300
Packard Bell	ixtreme M5720; ixtreme M5120

Test Standards :	
ETSI EN301 489-1 V1.6.1/2005-09	Standard for radio equipment and services; Common technical requirements
ETSI EN301 489-17 V1.2.1/2002-08	Standard for radio equipment and services; Specific conditions for 2.4GHz wideband transmission systems and 5GHz high performance RLAN equipment
EN55022: 2006	Limits and methods of measurement of radio disturbance characteristics of information technology equipment
EN 61000-3-2:2006	Electromagnetic compatibility(EMC) Part 3 :Limits Section 2 : Limits for harmonic current emissions (equipment input current $\leq 16A$ per phase)
EN 61000-3-3:1995+A1:2001+A2:2005	Electromagnetic compatibility(EMC) Part 3 :Limits Section 3 : Limits of voltage fluctuations and flicker in low-voltage supply systems for equipment with rated current $\leq 16A$
IEC 61000-4-2: 2001	Electrostatic discharge
IEC 61000-4-3: 2006	RF Field Strength susceptibility
IEC61000-4-4: 2004+Cor 1:2006+Cor 2:2007	Electrical Fast transients
IEC 61000-4-5: 2005	Surge
IEC61000-4-6: 2003+A1:2004+A2:2006	Conducted Susceptibility
IEC 61000-4-11: 2004	Dips / Voltage Interruption Variation

Stamp only for EMC Dept. Report

Signature:  4/15/09

Ken Lu
Manager

Date : Apr.15, 2009



The statement is based on a single evaluation of one sample of above mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab. logo.